



## CYCLONE for ARM® DEVICES

The Ultimate Production Programming Tool

### Overview

The **Cyclone for ARM devices** is a powerful **stand-alone** in-circuit programmer for ARM® Cortex™ devices from **Freescale, Atmel, STMicroelectronics, Texas Instruments, and NXP**. Communication with the PC occurs via Ethernet, USB, or Serial Port. Once the Cyclone is configured, programming operations may be completed in **one touch** with or without a PC.

P&E also hosts a rapidly growing library of compatible programming algorithms and welcomes requests for devices that are not currently supported.

### Production Power & Flexibility

The Cyclone's flexible set-up and intuitive software allow for a smooth transition to an easily scalable production programming environment. The Cyclone and the target being programmed may be local to the PC or connected remotely via Ethernet. Multiple Cyclones on your network can easily be detected and controlled from the same PC. In addition, the Cyclone for ARM devices has been specifically designed with features like voltage protection technology in order to withstand the rigors of a production environment.

In **Stand-Alone Mode**, the Cyclone for ARM devices is configured and loaded with one or more programming images. Control of the Cyclone may then be **automated** using a PC (e.g., for large production runs), or the Cyclone can be operated **independently of the PC** (e.g., for field updates). An **LCD screen** facilitates configuration and operation of the unit. The display's menu-based navigation allows the user to easily select the image to be programmed when the Cyclone for ARM devices contains multiple programming images.

### Supports Multiple ARM Cortex Manufacturers

- Freescale (Kineticis® K-series & L-series)
- Atmel (SAMxxx)
- STMicroelectronics (STM32)
- Texas Instruments (Stellaris™ LM3S/LM4)
- NXP (LPC1xxx)

### Applications

- Production Programming
- Testing
- Field Maintenance

### Hardware Features

- Ethernet, USB, and Serial Communication Interfaces
- Supports extremely fast communication speeds
- LCD Screen
- CompactFlash interface for expanded memory
- Multi-voltage support for targets ranging from 1.8 to 5 Volts
- Production environment ready with voltage protection technology
- Allows switching of the target's power supply

### Flash Programming Highlights

- Highly intuitive, fast in-circuit flash programming
- Capable of programming internal and external flash
- Multiple image support for programming of different images during production runs
- Trimming capabilities
- PC-controlled and stand-alone functions for programming and testing of units on production lines
- Can program dynamic data, such as serial numbers



©2013 P&E Microcomputer Systems, Inc. ARM is a registered trademark and Cortex is a trademark of ARM Limited. Stellaris is a trademark of Texas Instruments, Incorporated. Kineticis is a registered trademark of Freescale Semiconductor, Inc. All other brands or product names are the property of their respective owners.